

□ Membrane separation apparatus with means for suppressing substances adhering on the surfaces of the membranes

L20 ANSWER 44 OF 121 HCA COPYRIGHT 2002 ACS

AN 124:149427 HCA

IN Kabu, Masahiro; Ozaki, Tosha

PA Kubota Kk, Japan

SO Jpn. Kokai Tokkyo Koho, 3 pp.

CODEN: JKXXAF

DT Patent

LA Japanese

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
	-----	---	-----	-----	-----
PI	JP 07313851	A2	19951205	JP 1994-108833	19940524
AB	In the title app. comprising appropriately spaced plural membrane elements (e.g., ceramic <b>membrane</b> elements), and <b>cleaning</b> the surfaces of the membranes by passing <b>gas-liq. mixed sweeping flows</b> between adjacent membrane surfaces in vertical direction, flexible ribbons (e.g., synthetic resins or metal foils) are inserted in those flow paths in vertical direction, and the upper and lower ends on the ribbons are fixed by fixing members. Adhering of substances on the surfaces of the membranes is suppressed. Cleaning effect is increased. The membrane sepn. app. is suitable for for water purifn.				

BEST AVAILABLE COPY